



EFFECTIVE APRIL 15, 2011

Supersedes all previous information. Subject to change without notice.

EAST PENN manufacturing co., inc.

LYON STATION, PA 19536 • Phone: 610-682-6361 • Fax: 610-682-4781

Order Department Hotline: 610-682-4231

www.dekabatteries.com

| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | | WEIGHT (lbs) | MAXIMUM OVERALL DIMENSIONS | | | | | | Core Value | WARR Free / Pro Rata | FOOTNOTES |
|---|----------|-------------------|------|---------|-----------|--------------|----------------------------|--------|-------|-------|--------|-----|------------|----------------------------|------------|
| | | CCA | R.C. | REF. CA | 20 HR CAP | | LENGTH | | WIDTH | | HEIGHT | | | | |
| | | | | | | | in | mm | in | mm | in | mm | | | |
| 12-VOLT INTIMIDATOR® — AGM — VALVE REGULATED | | | | | | | | | | | | | | | |
| 34/78 | 9A78DT | 775 | 120 | 955 | 55 | 42.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 2,13,16,17 |
| 34/78 | 9A78CDT | 700 | 120 | 840 | 55 | 40.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 2,13,16,17 |
| 34 | 9A34 | 775 | 120 | 955 | 55 | 41 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 2,13,17 |
| 34R | 9A34R | 775 | 120 | 955 | 55 | 41 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 2,13,17 |
| 47 | 9A47 | 600 | 100 | 690 | 60 | 39 | 9-9/16 | 242 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 |
| 48 | 9A48 | 760 | 120 | 875 | 70 | 45.5 | 11 | 278 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 |
| 49 | 9A49 | 850 | 170 | 975 | 92 | 58.5 | 13-15/16 | 354 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 |
| 65 | 9A65 | 775 | 150 | 955 | 75 | 46 | 12 | 305 | 7-3/8 | 187 | 7-5/8 | 194 | 1.0 | 24/85 | 2,13,17 |
| 78 | 9A78 | 775 | 120 | 955 | 55 | 42.5 | 10-3/4 | 273 | 6-7/8 | 175 | 7-1/4 | 184 | 1.0 | 24/85 | 2,13,17 |
| 94R | 9A94R | 800 | 140 | 920 | 80 | 51.5 | 12-7/16 | 315 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 |
| 31 | 9A31 | 925 | 190 | 1060 | 100 | 63 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/36 | 2,13,17,X |
| 31P | 9A31P | 925 | 190 | 1060 | 100 | 63 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/36 | 2,13,17 |
| 34M | 9A34M | 775 | 120 | 955 | 55 | 41.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8-3/8 | 212 | 1.0 | 18/36 | 2,13,17,U |
| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | | WEIGHT (lbs) | MAXIMUM OVERALL DIMENSIONS | | | | | | Core Value | Free Replace / Pro Rata | FOOTNOTES |
| | | CCA | R.C. | REF. CA | 20 HR CAP | | LENGTH | | WIDTH | | HEIGHT | | | | |
| | | | | | | | in | mm | in | mm | in | mm | | | |
| 12-VOLT ULTIMATE® ADVANCED GENERATION / A3™ TECHNOLOGY | | | | | | | | | | | | | | | |
| 75/86 | 775DT | 690 | 90 | 820 | 34.5 | 9-3/4 | 248 | 7 | 178 | 8-1/8 | 206 | 1.0 | 24/85 | 14,16,17,18,22,37 | |
| 34/78 | 778DT | 850 | 115 | 1020 | 41 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 14,16,17,18,22,37 | |
| 24 | 724MF | 725 | 120 | 890 | 41 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 24/85 | 17,22 | |
| 24F | 724FMF | 725 | 120 | 890 | 41 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 24/85 | 17,22 | |
| 25 | 725MF | 625 | 95 | 775 | 35.5 | 9-3/4 | 248 | 6-7/8 | 175 | 8-7/8 | 225 | 1.0 | 24/85 | 17,22 | |
| 27 | 727MF | 840 | 140 | 1010 | 49.5 | 12-5/8 | 321 | 6-3/4 | 171 | 9 | 229 | 1.0 | 24/85 | 17,21 | |
| 27F | 727FMF | 840 | 140 | 1010 | 49.5 | 12-5/8 | 321 | 6-3/4 | 171 | 9 | 229 | 1.0 | 24/85 | 17,21 | |
| 34 | 734MF | 850 | 115 | 1020 | 38.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 17,18,22,37 | |
| 34R | 734RMF | 850 | 115 | 1020 | 38.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 24/85 | 17,18,22,37 | |
| 35 | 735MF | 625 | 95 | 775 | 35.5 | 9-3/4 | 248 | 6-7/8 | 175 | 8-7/8 | 225 | 1.0 | 24/85 | 17,22 | |
| 47 (H5) | 9AGM47 | 600 | 100 | 690 | 39 | 9-9/16 | 242 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 | |
| 48 (H6) | 9AGM48 | 760 | 120 | 875 | 45.5 | 11 | 278 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 | |
| 48 (H6) | 748MF | 730 | 120 | 895 | 42.5 | 11 | 278 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 17,22 | |
| 49 (H8) | 9AGM49 | 850 | 170 | 975 | 58.5 | 13-15/16 | 354 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 | |
| 65 | 765MF | 750 | 140 | 885 | 45.5 | 12 | 305 | 7-3/8 | 187 | 7-5/8 | 194 | 1.0 | 24/85 | 17,22 | |
| 75 | 775MF | 690 | 90 | 820 | 34.5 | 9-3/4 | 248 | 7 | 178 | 7-1/4 | 184 | 1.0 | 24/85 | 17,22 | |
| 78 | 778MF | 850 | 115 | 1020 | 39 | 10-3/4 | 273 | 6-7/8 | 175 | 7-1/4 | 184 | 1.0 | 24/85 | 17,22 | |
| 79 | 779MF | 840 | 140 | 1000 | 43 | 12-1/16 | 307 | 7-1/16 | 179 | 7-3/8 | 188 | 1.0 | 24/85 | 22 | |
| 86 | 786MF | 690 | 90 | 775 | 34.5 | 9 | 229 | 6-7/8 | 175 | 8-1/8 | 206 | 1.0 | 24/85 | 22 | |
| 94R (H7) | 9AGM94R | 800 | 140 | 920 | 51.5 | 12-7/16 | 315 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 24/85 | 13,17,22 | |
| 12-VOLT PREMIUM / A3™ TECHNOLOGY | | | | | | | | | | | | | | | |
| 75/86 | 675DT | 650 | 85 | 800 | 33 | 9-3/4 | 248 | 7 | 178 | 8-1/8 | 206 | 1.0 | 18/70 | 14,16,17,18,22,37 | |
| | 575DT | 540 | 85 | 670 | 32 | 9-3/4 | 248 | 7 | 178 | 8-1/8 | 206 | 1.0 | 18/60 | 14,16,17,18,22,37 | |
| 34/78 | 678DT | 690 | 110 | 820 | 36.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 18/70 | 14,16,17,18,22,37 | |
| | 578DT | 550 | 90 | 660 | 33.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 18/60 | 14,16,17,18,22,37 | |
| | 624MF | 675 | 115 | 850 | 40 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/70 | 17,22 | |
| | 524MF | 550 | 90 | 650 | 35.5 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/60 | 17,22 | |
| | 424MF | 460 | 70 | 575 | 32 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 12/50 | 17,22 | |
| 24F | 624FMF | 675 | 115 | 850 | 40 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/70 | 17,22 | |
| | 524FMF | 550 | 90 | 650 | 35.5 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/60 | 17,22 | |
| | 424FMF | 460 | 70 | 575 | 32 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 12/50 | 17,22 | |
| 25 | 525MF | 550 | 90 | 675 | 33.5 | 9-3/4 | 248 | 6-7/8 | 175 | 8-7/8 | 225 | 1.0 | 18/60 | 17,22 | |
| | 526MF | 540 | 80 | 665 | 29.5 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 18/60 | 17,18,22,37 | |
| | 426MF | 450 | 55 | 560 | 26 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 12/50 | 17,18,22,37 | |
| 26R | 526RMF | 540 | 80 | 665 | 29.5 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 18/60 | 17,18,22,37 | |
| | 426RMF | 450 | 55 | 560 | 26 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 12/50 | 17,18,22,37 | |
| 27 | 627MF | 710 | 120 | 860 | 45.5 | 12 | 305 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/70 | 21 | |
| 27F | 627FMF | 710 | 120 | 860 | 45.5 | 12-3/8 | 314 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/70 | 21 | |
| 34 | 634MF | 690 | 110 | 820 | 36.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 18/70 | 17,18,22,37 | |
| | 534MF | 550 | 90 | 690 | 33.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 18/60 | 17,18,22,37 | |
| 34R | 634RMF | 690 | 110 | 820 | 36.5 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 18/70 | 17,18,22,37 | |
| 35 | 535MF | 550 | 90 | 675 | 33.5 | 9-3/4 | 248 | 6-7/8 | 175 | 8-7/8 | 225 | 1.0 | 18/60 | 17,22 | |
| 36R | 636RMF | 650 | 120 | 800 | 42 | 10-1/4 | 260 | 7-1/4 | 184 | 8 | 203 | 1.0 | 18/70 | | |
| 40R (T6) | 640RMF | 650 | 105 | 810 | 37 | 11 | 278 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 | |
| 41 | 641MF | 650 | 100 | 800 | 38 | 11-9/16 | 293 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 22 | |
| 42/58R | 642/58R | 580 | 85 | 725 | 31.5 | 10 | 254 | 7-1/4 | 184 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 | |
| | 542/58R | 500 | 75 | 630 | 28 | 10 | 254 | 7-1/4 | 184 | 6-7/8 | 175 | 1.0 | 18/60 | 17,22 | |
| 42 | 642MF | 475 | 70 | 590 | 29 | 9-9/16 | 242 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | | |
| 45 | 545MF | 485 | 65 | 600 | 30.5 | 9-3/8 | 238 | 5-1/2 | 140 | 9 | 229 | 1.0 | 18/60 | | |
| 47 (H5) | 647MF | 600 | 95 | 750 | 36.5 | 9-9/16 | 242 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 | |
| 48 (H6) | 648MF | 700 | 120 | 875 | 42 | 11 | 278 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 | |
| 49 (H8) | 649MF | 900 | 185 | 1080 | 56.5 | 13-15/16 | 354 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 | |
| 50 | 650MF | 600 | 108 | 750 | 43 | 13-3/8 | 340 | 5-3/8 | 136 | 8-7/8 | 225 | 1.0 | 18/70 | 17 | |
| 51 | 551MF | 475 | 70 | 590 | 28 | 9-3/8 | 238 | 5 | 127 | 8-3/4 | 222 | 1.0 | 18/60 | 22 | |
| | 651RMF | 500 | 75 | 600 | 29 | 9-3/8 | 238 | 5 | 127 | 8-3/4 | 222 | 1.0 | 18/70 | 22 | |
| 51R | 551RMF | 475 | 70 | 590 | 28 | 9-3/8 | 238 | 5 | 127 | 8-3/4 | 222 | 1.0 | 18/60 | 22 | |
| | 655MF | 570 | 90 | 705 | 29.5 | 8-3/4 | 222 | 6 | 152 | 8-1/2 | 216 | 1.0 | 18/70 | 17,18 | |
| 55 | 658MF | 580 | 85 | 725 | 31.5 | 10 | 254 | 7-1/4 | 184 | 7 | 178 | 1.0 | 18/70 | 17,22 | |
| | 558MF | 500 | 75 | 630 | 29 | 10 | 254 | 7-1/4 | 184 | 7 | 178 | 1.0 | 18/60 | 17,22 | |
| 58R | 658RMF | 580 | 85 | 725 | 31.5 | 10 | 254 | 7-1/4 | 184 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 | |
| 59 | 659MF | 590 | 100 | 700 | 37 | 9-1/2 | 241 | 7-7/16 | 189 | 7-1/2 | 190 | 1.0 | 18/70 | 17 | |

| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | WEIGHT (lbs) WET | MAXIMUM OVERALL DIMENSIONS | | | | | | Core Value | Free Replace / Pro Rata | FOOTNOTES |
|--|---|-------------------|------|---------|---------------------|----------------------------|-----|---------|-----|---------|-----|------------|-------------------------|-----------------|
| | | CCA | R.C. | REF. CA | | LENGTH | | WIDTH | | HEIGHT | | | | |
| | | | | | | in | mm | in | mm | in | mm | | | |
| 12-VOLT PREMIUM / A3™ TECHNOLOGY | | | | | | | | | | | | | | |
| 64 | 664MF | 620 | 100 | 770 | 42 | 11-3/4 | 298 | 6-1/4 | 159 | 8-7/8 | 225 | 1.0 | 18/70 | |
| 65 | 665MF | 880 | 150 | 1040 | 45.5 | | | | | | | 1.0 | 18/70 | 17,22 |
| | 565MF | 675 | 130 | 890 | 41 | 12 | 305 | 7-3/8 | 187 | 7-5/8 | 194 | 1.0 | 18/60 | 17,22 |
| 70 | 570MF | 540 | 80 | 665 | 29.5 | 8-3/4 | 222 | 7 | 178 | 7-1/8 | 181 | 1.0 | 18/60 | 17,18,22,37 |
| 75 | 675MF | 650 | 85 | 800 | 33 | 9-3/4 | 248 | 7 | 178 | 7-1/4 | 184 | 1.0 | 18/70 | 17,22 |
| | 575MF | 540 | 85 | 670 | 32 | | | | | | | 1.0 | 18/60 | 17,22 |
| 78 | 678MF | 690 | 110 | 820 | 36.5 | 10-3/4 | 273 | 6-7/8 | 175 | 7-1/4 | 184 | 1.0 | 18/70 | 17,22 |
| | 578MF | 550 | 90 | 690 | 33.5 | | | | | | | 1.0 | 18/60 | 17,22 |
| 85 | 685MF | 650 | 110 | 775 | 35.5 | 9 | 229 | 6-7/8 | 175 | 8-1/8 | 206 | 1.0 | 18/70 | 22 |
| 86 | 586MF | 540 | 85 | 675 | 32 | 9 | 229 | 6-7/8 | 175 | 8-1/8 | 206 | 1.0 | 18/60 | 22 |
| 90 (T5) | 690MF | 600 | 90 | 745 | 33.5 | 9-9/16 | 242 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 |
| 91 (T6) | 691MF | 700 | 100 | 875 | 36.5 | 11 | 278 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 |
| 92 (T7) | 692MF | 650 | 130 | 780 | 37 | 12-1/2 | 317 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 |
| 93 (T8) | 693MF | 800 | 130 | 960 | 46.5 | 13-15/16 | 354 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 |
| 94R (H7) | 694RMF | 765 | 135 | 910 | 45 | 12-7/16 | 315 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 |
| 95R (H9) | 695RMF | 850 | 190 | 1020 | 64.5 | 15-1/2 | 394 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 |
| 96R | 696RMF | 600 | 90 | 745 | 33.5 | 9-9/16 | 242 | 6-7/8 | 175 | 6-7/8 | 175 | 1.0 | 18/70 | 17,22 |
| 97R (H5) | 697RMF | 600 | 95 | 750 | 36.5 | 9-9/16 | 242 | 6-7/8 | 175 | 7-1/2 | 190 | 1.0 | 18/70 | 17,22 |
| 101 | 6101MF | 650 | 110 | 810 | 36 | 10-1/4 | 260 | 7-1/16 | 179 | 6-11/16 | 170 | 1.0 | 18/70 | 22 |
| 121R | 6121RMF | 540 | 80 | 665 | 29.5 | 8-1/4 | 210 | 6-15/16 | 177 | 8-1/8 | 206 | 1.0 | 18/70 | |
| 124R | 6124RMF | 670 | 100 | 810 | 38 | 10-1/4 | 260 | 6-7/8 | 175 | 8-3/8 | 212 | 1.0 | 18/70 | 22 |
| 151R | 5151RMF | 330 | 55 | 440 | 19 | 7-1/4 | 184 | 4-15/16 | 125 | 8-3/4 | 222 | 1.0 | 18/60 | 17,22 |
| Miata | 8AMU1R | 320 | 45 | 400 | 25 | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 18/70 | 2,13,22,38,39 |
| 12-VOLT VALUE LINE MAINTENANCE-FREE | | | | | | | | | | | | | | |
| 75/86 | VL75DT | 475 | 60 | 590 | 32 | 9-3/4 | 248 | 7 | 178 | 8-1/8 | 206 | 1.0 | 6/55 | 14,16,17,22 |
| 34/78 | VL78DT | 525 | 80 | 650 | 32 | 10-3/4 | 273 | 6-7/8 | 175 | 8 | 203 | 1.0 | 6/55 | 14,16,17,22 |
| 24 | VL24 | 440 | 70 | 550 | 32 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 6/55 | 17,22 |
| 24F | VL24F | 440 | 70 | 550 | 32 | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 6/55 | 17,22 |
| 26 | VL26 | 440 | 55 | 550 | 26 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 6/55 | 17,22 |
| 26R | VL26R | 440 | 55 | 550 | 26 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 6/55 | 17,22 |
| 58 | VL58 | 440 | 70 | 550 | 27.5 | 10 | 254 | 7-1/4 | 184 | 7 | 178 | 1.0 | 6/55 | 17,22 |
| 65 | VL65 | 650 | 120 | 865 | 38.5 | 12 | 305 | 7-3/8 | 187 | 7-5/8 | 194 | 1.0 | 6/55 | 17,22 |
| 31 | VL31 | 650 | 130 | 800 | 49.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 6/30 | 19,22,X |
| 31P | VL31P | 650 | 130 | 800 | 49.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 6/30 | 19,22 |
| 12-VOLT VINTAGE VEHICLES & LIGHT COMMERCIAL | | | | | | | | | | | | | | |
| 3EE | 403E | 400 | 95 | 485 | 42 | 19-1/4 | 489 | 4-1/4 | 108 | 9 | 229 | 1.0 | 12/30 | 11,25 |
| 22NF | See page 2, Lawn Mower – Garden Tractor – Small Engine section. | | | | | | | | | | | | | |
| 29NF | 429NF | 390 | 90 | 465 | 41 | 12-7/8 | 327 | 5-1/2 | 140 | 9 | 229 | 1.0 | 12/30 | 11,15,25 |
| 53 | 353 | 290 | 62 | 360 | 32.5 | 13 | 330 | 4-3/4 | 121 | 8-3/8 | 213 | 1.0 | 12/20 | 11,15,25 |
| 6-VOLT LIGHT TRUCK — OLDER MODEL PASSENGER CARS | | | | | | | | | | | | | | |
| 2E | 402E | 620 | 190 | 750 | 42 | 19-1/4 | 489 | 4 | 102 | 8-7/8 | 225 | 1.0 | 12/20 | 11,15,25 |
| 19L | 319L | 440 | 120 | 560 | 26 | 8-1/4 | 210 | 6-3/4 | 171 | 7-1/2 | 191 | 1.0 | 12/20 | 11,15,25 |
| 8-VOLT COMMERCIAL SERVICE | | | | | | | | | | | | | | |
| 1 | 801 | 520 | 102 | 650 | 31.5 | 8-7/8 | 225 | 6-3/4 | 171 | 8-7/8 | 225 | 1.0 | 12/24 | 12,25 |
| 6-VOLT HEAVY-DUTY COMMERCIAL SERVICE | | | | | | | | | | | | | | |
| 1 | 901MF | 640 | 130 | 800 | 30 | 9 | 229 | 6-7/8 | 175 | 8-3/4 | 222 | 1.0 | 12/30 | 21,25 |
| 2 | 902 | 780 | 200 | 940 | 36.5 | 10-3/8 | 264 | 6-7/8 | 175 | 8-3/4 | 222 | 1.0 | 12/30 | 12,25 |
| 3EH | 93EH | 875 | 250 | 1035 | 47.5 | 19-1/4 | 489 | 4-1/4 | 108 | 10 | 254 | 1.0 | 12/30 | 12,25 |
| 4 | 904MF | 975 | 250 | 1170 | 47 | 12-1/2 | 318 | 6-7/8 | 175 | 9-1/2 | 241 | 1.5 | 12/30 | 21,25 |
| 5D | 905D | 880 | 250 | 1100 | 50 | 13-3/8 | 340 | 7-1/8 | 181 | 9-1/4 | 235 | 1.5 | 12/30 | 12,25 |
| 12-VOLT HEAVY-DUTY COMMERCIAL SERVICE | | | | | | | | | | | | | | |
| 3ET | 93ET | 500 | 120 | 625 | 48 | 19-1/4 | 489 | 4-1/4 | 108 | 9-7/8 | 251 | 1.0 | 12/30 | 12,25 |
| 4D | 904D | 1050 | 290 | 1280 | 99.5 | 20-3/4 | 527 | 8-1/2 | 216 | 10-1/8 | 258 | 3.0 | 12/30 | 12,17,25 |
| 4DLT | 94DLT | 850 | 240 | 1005 | 80 | 20 | 508 | 8-1/8 | 206 | 8-1/8 | 206 | 2.0 | 12/30 | 12,19,25 |
| 8D | 908D | 1400 | 430 | 1700 | 130 | | | | | | | 4.0 | 12/30 | 12,17,25 |
| | 708D | 1100 | 325 | 1340 | 117.5 | 20-3/4 | 527 | 11 | 279 | 10 | 254 | 4.0 | 12/30 | 12,17,25 |
| 17TF | 917TF | 530 | 140 | 630 | 58.5 | 17 | 432 | 6-7/8 | 175 | 8 | 203 | 1.5 | 12/30 | 11,15,19,25 |
| 28 | 928MF | 550 | 100 | 685 | 41.5 | 10-1/4 | 260 | 6-3/4 | 171 | 9-1/2 | 241 | 1.0 | 12/30 | 21,22,X |
| 30H | 930H | 650 | 150 | 800 | 51 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12/30 | 19,21,22 |
| 31 | 1231MF | 1000 | 190 | 1190 | 58 | | | | | | | 1.5 | 18/30 | 17,19,21,22,X |
| | 1131MF | 950 | 175 | 1140 | 56.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/30 | 17,19,21,22,X |
| | 1031MF | 760 | 170 | 910 | 54.5 | | | | | | | 1.5 | 18/30 | 19,21,22,X |
| | 931MF | 650 | 150 | 810 | 51 | | | | | | | 1.5 | 18/30 | 19,21,22,X |
| 31P | 1231PMF | 1000 | 190 | 1190 | 58 | | | | | | | 1.5 | 18/30 | 17,19,21,22 |
| | 1131PMF | 950 | 175 | 1140 | 56.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/30 | 17,19,21,22 |
| | 1031PMF | 760 | 170 | 910 | 54.5 | | | | | | | 1.5 | 18/30 | 19,21,22 |
| | 931PMF | 650 | 150 | 810 | 51 | | | | | | | 1.5 | 18/30 | 19,21,22 |
| 12-VOLT HEAVY-DUTY COMMERCIAL SEVERE SERVICE/DUAL PURPOSE | | | | | | | | | | | | | | |
| 31 | 7T31 | 730 | 190 | 940 | 62.5 | | | | | | | 1.5 | 18/30 | 19,21,22,43,X |
| 31P | 7T31P | 730 | 190 | 940 | 62.5 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/30 | 19,21,22,43 |
| 31 | DP31CS | 700 | 185 | 875 | 57 | | | | | | | 1.5 | 18/30 | 19,21,22,43,X |
| 12-VOLT HEAVY-DUTY COMMERCIAL — AGM — DEEP CYCLE / STARTING | | | | | | | | | | | | | | |
| 31 | 8A31 | 800 | 200 | 1000 | 69 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12/36 | 2,13,17,38,39,X |
| 12-VOLT LAWN MOWER — GARDEN TRACTOR — SMALL ENGINE CALCIUM MAINTENANCE-FREE | | | | | | | | | | | | | | |
| U1 | 11U1L | 350 | — | 410 | 19 | | | | | | | 0.5 | 6/12 | 22,Z |
| | 10U1L | 300 | — | 365 | 17 | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 6/12 | 22,Z |
| | 8U1L | 230 | — | 275 | 15.5 | | | | | | | 0.5 | 6/12 | 22,Z |
| | 7U1L | 195 | — | 235 | 15 | | | | | | | 0.5 | 6/12 | 22,Z |
| U1R | 10U1R | 300 | — | 365 | 17 | | | | | | | 0.5 | 6/12 | 22,Y |
| | 8U1R | 230 | — | 275 | 15.5 | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 6/12 | 22,Y |
| | 7U1R | 195 | — | 235 | 15 | | | | | | | 0.5 | 6/12 | 22,Y |
| U1L = left front positive; U1R = right front positive (with terminal side of battery to front) | | | | | | | | | | | | | | |
| 22F | 522FMF | 425 | 65 | 540 | 29.5 | 9-3/8 | 238 | 6-3/4 | 171 | 8-1/4 | 210 | 1.0 | 6/12 | |
| 22NF | 322NF | 360 | 58 | 430 | 29 | 9-3/8 | 238 | 5-1/2 | 140 | 9 | 229 | 0.5 | 6/12 | 12 |

| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | WEIGHT (lbs) | | LENGTH | | WIDTH | | HEIGHT | | Core Value | Free / Pro Rate | FOOTNOTES | | | | | | |
|---|---|-------------------|------|----------|--------------|--------|--------|----------|-------|--------|--------|--------|------------|--------------------|-----------|------------------|--------|-----|-----|------|--------------------|
| | | CCA | R.C. | REF. MCA | WET | in | mm | in | mm | in | mm | | | | | | | | | | |
| 12-VOLT MARINE / RV STARTING CALCIUM MAINTENANCE-FREE | | | | | | | | | | | | | | | | | | | | | |
| 24 | 24M7 | 800 | 130 | 1000 | 45 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 17,22,U | | | | | | | |
| | 24M6 | 675 | 115 | 820 | 40 | | | | | | | 1.0 | 12/24 | 17,22,U | | | | | | | |
| | 24M5 | 550 | 90 | 650 | 35.5 | | | | | | | 1.0 | 12/24 | 17,22,U | | | | | | | |
| | 24M4 | 460 | 70 | 575 | 32 | | | | | | | 1.0 | 12/24 | 17,22,U | | | | | | | |
| 27 | 27M6 | 840 | 182 | 1050 | 56 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 17,U | | | | | | | |
| 12-VOLT MARINE / RV DUAL PURPOSE STARTING / CYCLE SERVICE | | | | | | | | | | | | | | | | | | | | | |
| 24 | DP24 | 550 | 685 | 140 | 120 | 65 | 42 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 12,17,U | | | | | |
| 27 | DP27 | 650 | 810 | 175 | 150 | 80 | 49 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 12,17,U | | | | | |
| 31 | DP31DT | 700 | 875 | 205 | 185 | 100 | 57 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12/24 | 17,21,22,U | | | | | |
| 12-VOLT MARINE / RV DEEP CYCLE SERVICE | | | | | | | | | | | | | | | | | | | | | |
| 24 | DC24 | 500 | 625 | 150 | 130 | 75 | 45 | 10-3/4 | 273 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 11,17,35,U | | | | | |
| 27 | DC27 | 575 | 715 | 200 | 175 | 90 | 53 | 12-1/2 | 318 | 6-3/4 | 171 | 9-3/8 | 238 | 1.0 | 12/24 | 11,17,35,U | | | | | |
| 31 | DC31DT | 650 | 810 | 225 | 185 | 105 | 59 | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 12/24 | 11,17,21,22,35,U | | | | | |
| Note: The three "DC" deep cycle part numbers above include double insulated glass mat separators. | | | | | | | | | | | | | | | | | | | | | |
| ORDNANCE | | | | | | | | | | | | | | | | | | | | | |
| 2HN | See page 4, Dry Charged Batteries section | | | | | | | | | | | | | | | | | | | | |
| 4HN | | | | | | | | | | | | | | | | | | | | | |
| 6TL | 6TMF | 750 | 230 | 120 | 73 | 11-1/4 | 286 | 10-1/2 | 267 | 9 | 229 | 2.0 | 6/24 | 6,17,21,25 | | | | | | | |
| 6-VOLT FLOOR SCRUBBER AND SWEEPER | | | | | | | | | | | | | | | | | | | | | |
| 901 | 9C11 | 250 | 210 | 130 | 73 | 11-3/4 | 298 | 7 | 178 | 11-1/2 | 292 | 1.5 | 6/12 | 4,11,17,19,25,34,V | | | | | | | |
| | 8C11 | 235 | 190 | 120 | 66.5 | | | | | | | 1.5 | 6/12 | 4,11,17,19,25,34,V | | | | | | | |
| | 902 | 8C6V | 330 | 270 | 170 | | | | | | | 97.5 | 11-3/4 | 298 | 7 | 178 | 14-3/8 | 365 | 2.0 | 6/12 | 4,11,17,19,25,34,V |
| | 903 | 8L16 | 370 | 295 | 190 | | | | | | | 113 | 11-3/4 | 298 | 7 | 178 | 16-1/2 | 419 | 2.5 | 6/12 | 4,11,17,19,25,34,W |
| 12-VOLT FLOOR SCRUBBER AND SWEEPER | | | | | | | | | | | | | | | | | | | | | |
| 921 | 9C12 | 228 | 180 | 115 | 127 | 15-1/2 | 394 | 7 | 178 | 14-1/4 | 362 | 3.0 | 6/12 | 11,17,25,34,V | | | | | | | |
| | 8C12 | 195 | 160 | 90 | 116 | | | | | | | 3.0 | 6/12 | 11,17,25,34,V | | | | | | | |
| GOLF CAR — EV — MOTIVE POWER — DEEP CYCLE SERVICE | | | | | | | | | | | | | | | | | | | | | |
| GC2 | GC25 | 235 | 188 | 132 | — | 488 | 68 | 10-1/4 | 260 | 7-1/8 | 181 | 10-7/8 | 276 | 1.5 | 6/12 | 4,11,36,U | | | | | |
| | GC15 | 230 | 174 | 120 | — | 448 | 64 | | | | | | | 1.5 | 6/12 | 4,11,36,U | | | | | |
| | GC10 | 215 | 157 | 105 | — | 395 | 60.5 | | | | | | | 1.5 | 6/12 | 11,36,U | | | | | |
| GC2H | GC45 | 255 | 203 | 145 | — | 530 | 77 | 10-1/4 | 260 | 7-1/8 | 181 | 11-7/8 | 302 | 1.5 | 6/12 | 4,11,36,U | | | | | |
| GC8 | GC8V | 165 | 130 | 85 | 121 | 318 | 68 | 10-1/4 | 260 | 7-1/8 | 181 | 11-1/8 | 283 | 1.5 | 6/12 | 4,11,36,G | | | | | |
| | GC12V | 155 | — | 77 | 110 | 292 | 90 | 13-1/8 | 333 | 7-1/16 | 179 | 11-3/8 | 289 | 1.5 | 6/12 | 7,11,O | | | | | |
| 12-VOLT GOLF CAR STARTING BATTERY | | | | | | | | | | | | | | | | | | | | | |
| For gas engine golf cars with T881 terminal: | | | | | | | | | | | | | | | | | | | | | |
| 24/26 | 426G | 450 | 55 | 560 | 26 | 8-3/4 | 222 | 6-3/4 | 171 | 8 | 203 | 1.0 | 6/12 | 17,22,G | | | | | | | |
| AGM VALVE REGULATED | | | | | | | | | | | | | | | | | | | | | |
| U1 | 8AU1 | 200 | 240 | 48 | 54 | 32 | 24 | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 3/6 | 2,38,39,Y | | | | | |
| | 8AU1H | 200 | 240 | 48 | 54 | 32 | 24 | 8-5/16 | 211 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 3/6 | 2,17,38,39,Y | | | | | |
| 22NF | 8A22NF | 350 | 420 | 85 | 95 | 55 | 38.5 | 9-3/8 | 238 | 5-1/2 | 140 | 9-1/4 | 235 | 0.5 | 3/6 | 2,38,39,G | | | | | |
| 24M | 8A24M | 525 | 800 | 135 | 145 | 79 | 53 | 10-7/8 | 276 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/36 | 2,17,38,39,U | | | | | |
| | 8A24 | 525 | 800 | 135 | 145 | 79 | 53 | 10-7/8 | 276 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/36 | 2,17,38,39,G | | | | | |
| 24 | 8A24NH | 525 | 800 | 135 | 145 | 79 | 53 | 10-1/4 | 260 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/36 | 2,38,39,G | | | | | |
| | 8A27M | 580 | 900 | 175 | 185 | 92 | 63 | 12-3/4 | 324 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/36 | 2,17,38,39,U | | | | | |
| 27 | 8A27 | 580 | 900 | 175 | 185 | 92 | 63 | 12-3/4 | 324 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/36 | 2,17,38,39,G | | | | | |
| 31M | 8A31DTM | 800 | 1000 | 200 | 210 | 105 | 69 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/8 | 238 | 1.5 | 12/36 | 2,16,17,38,39,U | | | | | |
| 4D | 8A4D | 1110 | 1420 | 380 | 413 | 198 | 129 | 20-3/4 | 527 | 8-1/2 | 216 | 10 | 254 | 3.0 | 12/36 | 2,17 | | | | | |
| 8D | 8A8D | 1450 | 1800 | 480 | 517 | 245 | 158 | 20-3/4 | 527 | 11 | 279 | 10 | 254 | 4.0 | 12/36 | 2,17 | | | | | |
| GC2 | 8AGC2 | 680 | 900 | 380 | 409 | 190 | 69.5 | 10-1/4 | 260 | 7-1/8 | 181 | 10-7/8 | 276 | 1.5 | 3/12 | 2,U | | | | | |
| GEL VALVE REGULATED | | | | | | | | | | | | | | | | | | | | | |
| U1 | 8GU1 | 200 | 290 | 44 | 47 | 31.6 | 23.4 | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 3/6 | 4,38,39,Y | | | | | |
| | 8GU1H | 200 | 290 | 44 | 47 | 31.6 | 23.4 | 8-5/16 | 211 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 3/6 | 4,17,38,39,Y | | | | | |
| 22NF | 8G22NF | 210 | 300 | 77 | 82 | 51 | 37 | 9-3/8 | 238 | 5-1/2 | 140 | 9-1/4 | 235 | 0.5 | 3/6 | 4,38,39,G | | | | | |
| 24M | 8G24M | 410 | 575 | 132 | 140 | 73.6 | 52.5 | 10-7/8 | 276 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/60 | 4,17,38,39,U | | | | | |
| | 8G24 | 335 | 470 | 132 | 140 | 73.6 | 52 | 10-7/8 | 276 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/60 | 4,17,38,39,G | | | | | |
| 24 | 8G24NH | 335 | 470 | 132 | 140 | 73.6 | 52 | 10-1/4 | 260 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/60 | 4,38,39,G | | | | | |
| | 8G24SS | 335 | 470 | 132 | 140 | 73.6 | 52 | 10-1/4 | 260 | 6-3/4 | 171 | 8-1/4 | 210 | 1.0 | 12/60 | 4,38,39,C | | | | | |
| 27M | 8G27M | 505 | 700 | 160 | 170 | 88 | 63.2 | 12-3/4 | 324 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/60 | 4,17,38,39,U | | | | | |
| 27 | 8G27 | 400 | 550 | 160 | 170 | 88 | 62.7 | 12-3/4 | 324 | 6-3/4 | 171 | 9-7/8 | 251 | 1.0 | 12/60 | 4,17,38,39,G | | | | | |
| | 8G27/T876 | 400 | 550 | 160 | 170 | 88 | 62.7 | 12-3/4 | 324 | 6-3/4 | 171 | 9-1/4 | 235 | 1.0 | 12/60 | 4,17,38,39,B | | | | | |
| 30H | 8G30H | 450 | 640 | 180 | 190 | 97.6 | 69.5 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/4 | 248 | 1.5 | 12/60 | 4,17,38,39,B | | | | | |
| 31M | 8G31DTM | 550 | 780 | 180 | 190 | 97.6 | 70 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/8 | 238 | 1.5 | 12/60 | 4,16,17,38,39,U | | | | | |
| 31 | 8G31 | 450 | 640 | 180 | 190 | 97.6 | 69.5 | 12-15/16 | 329 | 6-3/4 | 171 | 9-3/8 | 238 | 1.5 | 12/60 | 4,17,38,39,X | | | | | |
| 34R | 8G34R | 300 | 420 | 90 | 96 | 60 | 41.5 | 10-3/16 | 259 | 6-5/8 | 169 | 7 | 178 | 1.0 | 12/60 | 4,38,39,C | | | | | |
| | 8G40C | 225 | 325 | 59 | 63 | 40 | 31.7 | 7-3/4 | 197 | 6-5/8 | 168 | 6-7/8 | 175 | 0.5 | 3/6 | 4,38,39,C | | | | | |
| 4D | 8G4D | 970 | 1245 | 375 | 395 | 183 | 127 | 20-3/4 | 527 | 8-1/2 | 216 | 10 | 254 | 3.0 | 12/60 | 4,17,38,39 | | | | | |
| 8D | 8G8D | 1150 | 1470 | 475 | 500 | 225 | 157 | 20-3/4 | 527 | 11 | 279 | 10 | 254 | 4.0 | 12/60 | 4,17,38,39 | | | | | |
| GC2 | 8GGC2 | 585 | 850 | 345 | 375 | 180 | 68.4 | 10-1/4 | 260 | 7-1/8 | 181 | 10-7/8 | 276 | 1.5 | 3/12 | 4,38,39,U | | | | | |
| GC8 | 8G8VGC | 400 | 575 | 250 | 270 | 140 | 69.5 | 10-1/4 | 260 | 7-1/8 | 181 | 10-7/8 | 276 | 1.5 | 3/12 | 4,U | | | | | |

| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | | WEIGHT | | LENGTH | | WIDTH | | HEIGHT | | Core Value | Free / Pro Rata | FOOTNOTES |
|---|----------|-------------------|----------------|-----------|-------|--------|------|--------|-----|--------|-----|--------|-----|------------|-----------------|----------------|
| | | CCA | 10 HR CAPACITY | | | KGS | LBS | in | mm | in | mm | in | mm | | | |
| POWER SPORTS AGM VALVE REGULATED | | | | | | | | | | | | | | | | |
| | ETX9 | 120 | 8 | | | 2.9 | 6.3 | 5-7/8 | 150 | 3-7/16 | 88 | 4-3/16 | 106 | 0.2 | 3/12 | 2,38,39 |
| | ETX12 | 180 | 10 | | | 4.3 | 9.4 | 5-7/8 | 150 | 3-7/16 | 88 | 5-1/8 | 130 | 0.2 | 3/12 | 2,38,39 |
| | ETX14 | 220 | 12 | | | 5.4 | 12 | 5-7/8 | 150 | 3-7/16 | 88 | 5-3/4 | 145 | 0.2 | 3/12 | 2,38,39,42,75 |
| | ETX14L | 220 | 12 | | | 5.4 | 12 | 5-7/8 | 150 | 3-7/16 | 88 | 5-3/4 | 145 | 0.2 | 3/12 | 2,38,39 |
| | ETX15 | 220 | 14 | | | 5 | 11 | 5-1/4 | 134 | 3-1/2 | 90 | 6-9/16 | 166 | 0.2 | 3/12 | 2,38,39,42,76 |
| | ETX15L | 220 | 14 | | | 5 | 11 | 5-1/4 | 134 | 3-1/2 | 90 | 6-9/16 | 166 | 0.2 | 3/12 | 2,38,39 |
| | ETX16 | 325 | 19 | | | 7.7 | 17 | 6-7/8 | 175 | 4 | 100 | 6-1/8 | 155 | 0.2 | 3/12 | 2,38,39,42,74 |
| | ETX16L | 325 | 19 | | | 7.7 | 17 | 6-7/8 | 175 | 4 | 100 | 6-1/8 | 155 | 0.2 | 3/12 | 2,38,39,42,74 |
| | ETX18L | 340 | 20 | | | 8.2 | 18 | 8-1/8 | 206 | 3-9/16 | 91 | 6-3/8 | 163 | 0.2 | 3/12 | 2,38,39 |
| | ETX20L | 310 | 17.5 | | | 7 | 15.5 | 6-7/8 | 175 | 3-7/16 | 88 | 6-1/8 | 155 | 0.2 | 3/12 | 2,38,39 |
| | ETX30L | 400 | 26 | | | 9.8 | 21.7 | 6-5/8 | 168 | 5-3/16 | 131 | 6-7/8 | 175 | 0.2 | 3/12 | 2,38,39 |
| | ETX30LA | 400 | 26 | | | 9.8 | 21.7 | 6-5/8 | 168 | 5-3/16 | 131 | 7-3/4 | 197 | 0.2 | 3/12 | 2,38,39,78 |
| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | | WEIGHT | | LENGTH | | WIDTH | | HEIGHT | | Core Value | Free / Pro Rata | FOOTNOTES |
| | | CCA | RES. CAP. | REF. CA | VOLTS | DRY | | in | mm | in | mm | in | mm | | | |
| DRY CHARGED BATTERIES | | | | | | | | | | | | | | | | |
| 24 | 624MFD | 675 | 115 | 850 | 12 | 26 | | 10-3/4 | 273 | 6-3/4 | 171 | 9 | 229 | 1.0 | 18/70 | 17,23 |
| 4D | 904DY | 1050 | 290 | 1280 | 12 | 58 | | 20-3/4 | 527 | 8-1/2 | 216 | 10-1/8 | 258 | 3.0 | 12/30 | 12,17,25 |
| 8D | 908DY | 1400 | 430 | 1700 | 12 | 80 | | 20-3/4 | 527 | 11 | 279 | 10 | 254 | 4.0 | 12/30 | 12,17,25 |
| 31 | 1231MFD | 1000 | 190 | 1190 | 12 | 43 | | 13 | 330 | 6-3/4 | 171 | 9-1/2 | 241 | 1.5 | 18/30 | 19,21,22,X |
| U1 | 8U1LD | 230 | — | 275 | 12 | 10.5 | | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 6/12 | 8,22,Z |
| U1R | 8U1RD | 230 | — | 275 | 12 | 10.5 | | 7-3/4 | 197 | 5-1/8 | 130 | 7-1/4 | 184 | 0.5 | 6/12 | 8,22,Y |
| GROUP NO. | PART NO. | PERFORMANCE LEVEL | | | | WEIGHT | | LENGTH | | WIDTH | | HEIGHT | | Core Value | Free / Pro Rata | FOOTNOTES |
| | | CCA | RES. CAP. | 20 HR CAP | VOLTS | DRY | | in | mm | in | mm | in | mm | | | |
| DRY CHARGED ORDNANCE BATTERIES | | | | | | | | | | | | | | | | |
| 2HN | 2HND | 400 | 75 | 45 | 12 | 25 | | 10-1/4 | 260 | 5-1/4 | 133 | 9 | 229 | 1.0 | 6/24 | 12,21,25,32 |
| 4HN | 4HND | 235 | 28 | 21 | 24 | 27.5 | | 10-1/4 | 260 | 5-1/4 | 133 | 9 | 229 | 1.0 | 6/24 | 11,17,21,25,32 |
| 6TL | 6TMFD | 750 | 230 | 120 | 12 | 52 | | 11-1/4 | 286 | 10-1/2 | 267 | 9 | 229 | 2.0 | 6/24 | 6,17,21,25 |



- B. Flag terminal w/ 3/8" diameter hole (T876)
C. 1/4" x 20 Copper Insert Terminal
F. Standing upright terminal w/ 3/8" diameter hole (T877)
G. Offset post w/ horizontal hole, stainless steel 5/16" bolt and hex nut (T881)
O. Offset post w/ vertical stainless steel 5/16" stud and hex nut (T872)
T. Heavy Duty L terminal w/ 3/8" diameter hole (T975)
U. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs & hex nuts
V. Molded-in offset SAE post and vertical 5/16" NEG., 5/16" POS. stainless steel studs
W. "L" type terminal w/ 5/16" diameter hole (T882)
X. 3/8" x 16 stainless steel stud posts
Y. Small L terminal with round holes
Z. Small L terminal with square holes

- All batteries are maintenance-free calcium grids except where noted
- All batteries manufactured in polypropylene cases and covers except where noted
- All batteries manufactured in black case and black cover except where noted
- All batteries, except Power Sports, have SAE automotive post unless noted
- Warranty is suggested months
- All weights are approximate weight
- MCA and CA ratings @ 32°F for comparison only
- All ratings except CCA and RC are "nominal"
- Ratings conform to B.C.I. specifications
- Dry = up to 10% reduced capacity
- 16. Dual terminal universal design
- 17. Includes handle
- 18. Includes top adapter
- 19. Includes lifting ledges
- 20. Hard rubber, multi-cell cover construction
- 21. Anchor lock elements
- 22. Flush manifold vented cover
- 23. Flush manifold vented cover when shipped wet, standard cover when shipped dry
- 25. With individual vent caps
- 32. Available dry charged only
- 34. Ratings after 15 cycles
- 35. Deduct 15% from CCA and CA rating shown to allow for double insulation (glass mat)
- 36. Peak performance capacity
- 37. For height with adapter add 7/8" (22mm)
- 38. "Non-spillable" defined by DOT (Department of Transportation) definitions
- 39. "Non-spillable" defined by ICAO (International Civil Aviation Organization) and IATA (International Air Transport Association) definitions
- 42. Height without adapter
- 43. Warranty is 12 months in deep cycle service
- 74. Shipped with 20mm adapter
- 75. Shipped with two (2) 17mm adapters
- 76. Shipped with 10mm adapter
- 78. Shipped with 22mm height adapter

FOOTNOTES

- Black cover / Gray case
- Gray cover / Gray case
- Black cover / Brown Case
- Dark blue cover / Dark blue case
- Dry charged batteries have black covers & white cases
- Low maintenance-low antimony grids
- Hybrid construction
- Absorbed Glass Mat technology
- Centerline terminal posts
- Hard rubber, one-piece cover construction